4 of responding to a disruption [detected by the client processing system during] in

5 communication[with the modem], the method comprising:

6   terminating communication with the [server] second processing system in

7 response to a disruption on the telephone line;

8   establishing an on-hook condition on the telephone line; and

9   waiting for a ring signal.

In claim 4, line 5, please delete "server" and substitute --second processing system-- in place thereof.

In claim 5, line 10, please delete "server" and substitute --second processing system-- in place thereof.

In claim 6, line 1, please delete "step" and substitute --steps-- in place thereof.

In claim 6, line 5, please delete "server" and substitute --second processing system-- in place thereof.

In claim 14, line 1, please delete "modem" and substitute --communication device-- in place thereof.

In claim 14, line 2, please delete "modem" and substitute --communication device-- in place thereof.

In claim 14, line 4, please delete "modem" and substitute --communication device-- in place thereof.

In claim 14, line 9, please delete "modem" and substitute --communication device-- in place thereof.

In claim 25, line 10, please delete "an interactive" and substitute --a graphical-- in place thereof.

[Please add the following new claims:]

2

35. (New) A method according to claim 6, wherein the first processing system includes a memory, the method further comprising the steps of:

in response to the disruption, storing in the memory information representing a current status; and

upon re-establishing communication with the second processing system, automatically re-establishing said current status using the information stored in the memory.

36. (New) A method according to claim 35, wherein the first processing system is configured for browsing the World Wide Web, and wherein the information representing said current status represents a Web browsing state of the first processing system when the disruption was detected.

37. (New) A method according to claim 7, further comprising the steps of:

before terminating communication with the server processing system, storing in the client processing system information representing a current state of the client processing system when the disruption was detected; and

upon re-establishing communication with the second processing system, re-establishing said current state of the client processing system using the stored information.

38. (New) A method according to claim 37, wherein the client processing system is configured for browsing the World Wide Web, and wherein the information representing said current state represents a browsing state of the client processing system when the disruption was detected.

39. (New) A method according to claim 14, further comprising the steps of:

3

2   in response to the disruption, storing in the client processing system

3   information identifying a current state of the client processing system at a time of

4   the disruption; and

5   upon re-establishing communication with the communication device,

6   automatically resuming said current state using the stored information.

40. (New) A method according to claim 39, wherein the client processing system is

2   configured for browsing the World Wide Web at the time of the disruption, and

3   wherein the information representing said current state represents a browsing state

4   of the client processing system at the time of the disruption.

1   41. (New) A method according to claim 14, wherein the communications device

2   comprises a modem.

1   42. (New) A method according to claim 14, wherein the communications device

2   comprises an Integrated Services Digital Network (ISDN) adapter.

1   43. (New) A method according to claim 25, wherein the processor is further

2   configured to cause the client system to allow the user to navigate through a

3   plurality of hypertext-based documents.